



MATERIAL SAFETY DATA SHEET



5250-A Naiman Parkway, Solon, OH 44139
888-567-2206 • www.chromate.com

FOR CHEMICAL
EMERGENCY
Call Chemtrec day/night:
1-800-424-9300

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: Air Tool Conditioner
RED LION PART NUMBER: 74136
PRODUCT TYPE: Cleaner
CHEMICAL FAMILY: N/A

DATE PREPARED: 2/15/07

CHROMATE INDUSTRIAL CORPORATION
5250-A Naiman Parkway, Solon, OH 44139 • (888) 567-2206

2. COMPOSITION / INFORMATION ON INGREDIENTS

CHEMICAL NAME	% BY WEIGHT	OSHA PEL	ACGIH TLV	STEL	VAPOR PRESSURE	CAS #
Propane	10	1000 ppm	2500 ppm	N/D	760 mm	74-98-6
Butane	10	800 ppm	800 ppm	N/D	760 mm	106-97-8
Mineral Spirits (Odorless)	40	100 ppm	100 ppm	N/D	1 mm	64741-65-7
Kerosine, Petroleum	7	N/A	N/A	N/D	0.7 mm	8008-20-6
Tetrachloroethylene	17	25 ppm	25 ppm	100 ppm	18 mm	127-18-4
Mineral Oil	16	5mg/m ³ as Mist	5mg/m ³ as Mist	N/D	N/D	64741-88-4

* An asterisk (*) indicates the toxic chemicals subject to the reporting requirements of Section 313 of the Emergency Planning and Community Right-to-Know Act of 1986 and 40 CFR 372.

3. HAZARDS IDENTIFICATION

PRIMARY ROUTES OF ENTRY: Inhalation, Skin, Eyes

EFFECTS OF OVEREXPOSURE:

INHALATION: Irritation of the upper respiratory system. May cause nervous system depression. Extreme overexposure may result in unconsciousness and possibly death. Headache, dizziness, nausea and loss of coordination are indications of excessive exposure to vapors or spray mists.

SKIN CONTACT: Prolonged or repeated exposure may cause irritation.

Redness and itching or burning sensation may indicate excessive skin exposure.

EYE CONTACT: Irritation. Redness and itching or burning sensation may indicate excessive eye exposure.


MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE: None generally recognized.

CHRONIC HEALTH HAZARDS: Reports have associated repeated and prolonged overexposure to solvents with permanent brain and nervous system damage. Tetrachloroethylene, listed by NTP and IARC as an animal carcinogen and by OSHA as a potential human carcinogen, produced liver tumors and leukemia in rats and lung tumors in mice. Human epidemiological evidence is conflicting and inconclusive.

HAZARD RATINGS

NFR: FLAMMABILITY

HMIS: 2 HEALTH



4. FIRST AID MEASURES

EMERGENCY FIRST AID PROCEDURES:

INHALATION: If affected, remove from exposure. Restore breathing. Keep warm and quiet.

INGESTION: DO NOT INDUCE VOMITING. Get medical attention immediately.

SKIN CONTACT: Wash affected area thoroughly with soap and water. Remove contaminated clothing and launder before re-use.

EYE CONTACT: Flush eyes with large amounts of water for 15 minutes. Get medical attention.

5. FIRE FIGHTING MEASURES

FLASH POINT (METHOD USE): Propellant <0°F FLAMMABLE LIMITS: LEL 0.7 UEL 9.5

EXTINGUISHING MEDIA: Carbon dioxide, foam, dry chemical.

FIRE FIGHTING PROCEDURES: Full protective equipment including self-contained breathing apparatus should be used. Water spray may be ineffective. If water is used, fog nozzles are preferable. Water may be used to cool closed containers to prevent pressure build-up and possible autoignition or explosion when exposed to extreme heat.

UNUSUAL AND EXPLOSION HAZARDS: Containers may explode when exposed to extreme heat. Application to hot surfaces requires special precautions. During emergency conditions overexposure to decomposition products may cause a health hazard. Symptoms may not be immediately apparent. Obtain medical attention.

6. ACCIDENTAL RELEASE MEASURES

SPILLS OR LEAKS: Remove all sources of ignition. Ventilate the area. Remove with inert absorbent.

7. HANDLING AND STORAGE

SPECIAL PRECAUTIONS: Keep away from heat, sparks and open flame. Vapors will accumulate readily and may ignite explosively. During use and until all vapors are gone: Keep area ventilated – Do not smoke – Extinguish all flames, pilot lights and heaters – Turn off stoves, electric tools and appliances, and any other sources of ignition. Consult NFPA Code. Use approved bonding and grounding procedures. Contents under pressure. Do not puncture, incinerate or expose to temperature above 120°F. Heat from sunlight, radiators, stoves, hot water and other heat sources could cause container to burst. Do not take internally. Keep out of the reach of children. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

PRECAUTIONS TO BE TAKEN IN USE: Use only with adequate ventilation. Avoid breathing vapor and spray mist. Avoid contact with skin and eyes. Wash hands after using.

RESPIRATORY PROTECTION: If personal exposure cannot be controlled below applicable limits by ventilation, wear a properly fitted organic vapor/particulate respirator approved by NIOSH/MSHA for protection against materials in Section II.

EYE PROTECTION: Wear safety spectacles with unperforated sideshields.

OTHER EQUIPMENT: None required for normal application of aerosol products where minimal skin contact is expected. For long or repeated contact, wear chemical resistant gloves.

EXPOSURE GUIDELINES: Local exhaust preferable. General exhaust acceptable if the exposure to materials in Section II is maintained below applicable exposure limits. Refer to OSHA Standards 1910.94, 1910.107, 1910.108.

9. PHYSICAL AND CHEMICAL PROPERTIES

BOILING POINT: <0°F to 572°F <-18 to 300°C

VAPOR PRESSURE PSIG at 70°F: N/D

VAPOR DENSITY (AIR = 1): Heavier than Air

SOLUBILITY IN WATER: N/A

PERCENT VOLATILE BY VOLUME: 85%

APPEARANCE AND ODOR: Red, Solvent

PRODUCT WEIGHT: 6.47 lb./gal. 775 g/l

SPECIFIC GRAVITY (H₂O = 1): 0.78

MELTING POINT: N/A **pH:** 7.0

EVAPORATION RATE (BUTYL ACETATE = 1): Faster than Ether

VOLATILE WEIGHT: 48.53% (less Water and Federally Exempt Solvents)

FORM: Liquid **VOLATILE COMPONENTS:** N/D

10. STABILITY AND REACTIVITY

STABILITY: Stable

CONDITIONS TO AVOID: None known

HAZARDOUS POLYMERIZATION: Will not occur

INCOMPATIBILITY (MATERIALS TO AVOID): None known

HAZARDOUS DECOMPOSITION OR BYPRODUCTS: By fire: carbon dioxide, carbon monoxide, hydrogen chloride

11. TOXICOLOGICAL INFORMATION

EYE: No data available.

SKIN: No data available.

INGESTION: No data available.

INHALATION: No data available.

SUBCHRONIC: No data available.

TERATOLOGY: No data available.

REPRODUCTION: No data available.

MUTAGENICITY: No data available.

CARCINOGENICITY:

NTP: Tetrachloroethylene **IARC MONOGRAPH:** Tetrachloroethylene **OSHA REGULATED:** Tetrachloroethylene

CALIFORNIA PROPOSITION 65:

WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.

CHEMICAL NAME	CAS #
Propane	74-98-6
Butane	106-97-8
Mineral Spirits Odorless	64741-65-7
Kerosene, Petroleum	8008-20-6
Tetrachloroethylene	127-18-4
Mineral Oil	64741-88-4

12. ECOLOGICAL INFORMATION

ECOTOXICOLOGICAL INFORMATION: No data available.

CHEMICAL FATE INFORMATION: No data available.

13. DISPOSAL CONSIDERATIONS

WASTE DISPOSAL METHOD: Waste from this product may be hazardous as defined under the Resource Conservation and Recovery Act (RCRA) 40 CFR 261. Waste must be tested for ignitability to determine the applicable EPA hazardous waste numbers. Do not incinerate.

Depressurize container. Dispose of in accordance with Federal, State and Local regulations regarding pollution. This product contains tetrachloroethylene, a highly volatile solvent which is a toxic waste as defined under the Resource Conservation and Recovery Act (RCRA) 40 CFR 261. In normal use this chemical will quickly evaporate, however grease or other residue removed by this product may contain sufficient tetrachloroethylene to be classified as a toxic waste.

14. TRANSPORT INFORMATION

TRANSPORTATION REQUIREMENTS (49CFR172-101)

D.O.T. CLASSIFICATION: Consumer Commodity ORM-D

D.O.T. SHIPPING NAME: None

15. REGULATORY INFORMATION

EXPOSURE LIMITS: No data available.

16. OTHER INFORMATION

The information contained herein is based on data considered accurate. However, no warranty is expressed or implied regarding the accuracy of these data or the results to be obtained from the use thereof. Vendor assumes no responsibility for injury to vendee or third persons proximately caused by the material if reasonable safety procedures are not adhered to as stipulated in this MSDS. Additionally, vendor assumes no responsibility for injury to vendee or third persons proximately caused by abnormal use of the material even if reasonable safety procedures are followed. Furthermore, vendee assumes the risk in his use of the material.