



MATERIAL SAFETY DATA SHEET

CHROMATE INDUSTRIAL CORPORATION®
100 DaVinci Drive, Bohemia, New York 11716 • 888-567-2206 • www.chromate.com

FOR CHEMICAL EMERGENCY
Call Chemtrec day/night:
1-800-424-9300

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: Baby Powder Odor Eliminator
RED LION PART NUMBER: 74166
PRODUCT TYPE: Odor Control
CHEMICAL FAMILY: N/A

DATE PREPARED: 2/9/06

CHROMATE INDUSTRIAL CORPORATION
100 DaVinci Drive, Bohemia, NY 11716 • (888) 567-2206

2. COMPOSITION / INFORMATION ON INGREDIENTS

CHEMICAL NAME	% BY WEIGHT	OSHA PEL	ACGIH TLV	STEL	VAPOR PRESSURE	CAS #
Propane	20	1000 ppm	2500 ppm	N/D	760 mm	74-98-6
Butane	9	800 ppm	800 ppm	N/D	760 mm	106-97-8
Acetone	68	1000 ppm	500 ppm	750 PPM	180 mm	67-64-1
Odorant	3	N/D	N/D	N/D	1 mm	Proprietary

* An asterisk (*) indicates the toxic chemicals subject to the reporting requirements of Section 313 of the Emergency Planning and Community Right-to-Know Act of 1986 and 40 CFR 372.

3. HAZARDS IDENTIFICATION

PRIMARY ROUTES OF ENTRY: Inhalation, Ingestion, Skin, Eyes

EFFECTS OF OVEREXPOSURE:

INHALATION: Irritation of the upper respiratory system. May cause nervous system depression. Extreme overexposure may result in unconsciousness and possibly death. Headache, dizziness, nausea, and loss of coordination of indications of excessive exposure to vapors or spray mists.

INGESTION: Vomiting. Aspiration hazard if swallowed.

SKIN CONTACT: Prolonged or repeated exposure may cause irritation.

Redness and itching or burning sensation may indicate excessive skin exposure;


EYE CONTACT: Irritation. Redness and itching or burning sensation may indicate eye exposure.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE: None generally recognized.

CHRONIC HEALTH HAZARDS: Reports have associated repeated and prolonged exposure to solvents with permanent brain and nervous system damage.

HAZARD RATINGS

NFR: FLAMMABILITY



HMS:

2	HEALTH
4	FLAMMABILITY
0	REACTIVITY
B	PROTECTION

4. FIRST AID MEASURES

EMERGENCY FIRST AID PROCEDURES:

INHALATION: Do not induce vomiting. Get medical attention immediately.

INGESTION: If affected, remove from exposure. Restore breathing. Keep warm and quiet.

SKIN CONTACT: Wash affected area thoroughly with soap and water. Remove contaminated clothing and launder before re-use.

EYE CONTACT: Flush eyes with large amounts of water for 15 minutes. Get medical attention.

5. FIRE FIGHTING MEASURES

FLASH POINT (METHOD USE): Propellant <0°F **FLAMMABLE LIMITS:** LEL 1.0 UEL 12.8

EXTINGUISHING MEDIA: Carbon Dioxide, Dry Chemical, Foam

FIRE FIGHTING PROCEDURES: Full protective equipment including self-contained breathing apparatus should be used. Water may be used to cool closed containers to prevent pressure build-up and possible autoignition or explosion when exposed to extreme heat.

UNUSUAL AND EXPLOSION HAZARDS: Containers may explode when exposed to extreme heat. Application to hot surfaces requires special precautions. During emergency conditions, overexposure to decomposition products may cause a health hazard. Symptoms may not be immediately apparent. Obtain medical attention.

6. ACCIDENTAL RELEASE MEASURES

SPILLS OR LEAKS: Remove all sources of ignition. Ventilate the area. Remove with inert absorbent.

7. HANDLING AND STORAGE

SPECIAL PRECAUTIONS: Keep away from heat, sparks and open flame. Vapors will accumulate readily and may ignite explosively. During use and until all vapors are gone: Keep area ventilated – Do not smoke – Extinguish all flames, pilot lights, and heaters – Turn off stoves, electric tools and appliances, and any other sources of ignition. Consult NFPA Code. Use approved Bonding and Grounding procedures. Contents under pressure. Do not puncture, incinerate, or expose to temperature above 120°F. Heat from sunlight, radiators, stoves, hot water, and other heat sources could cause container to burst. Do not take internally. Keep out of the reach of children.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

PRECAUTIONS TO BE TAKEN IN USE: Use only with adequate ventilation. Avoid contact with skin and eyes. Avoid breathing vapor and spray mist. Wash hands after using.

VENTILATION: Local exhaust preferable. General exhaust acceptable if the exposure to materials in Section 2 is maintained below applicable exposure limits. Refer to OSHA Standards 1910.94, 1910.107, 1910.108.

RESPIRATORY: If personal exposure cannot be controlled below applicable limits by ventilation, wear a properly fitted organic vapor/particulate respirator approved by NIOSH/MSHA for protection against materials in Section 2.

PROTECTIVE GLOVES: None required for normal application of aerosol products where minimal skin contact is expected. For long or repeated contact, wear chemical resistant gloves.

EYE PROTECTION: Wear safety spectacles with unperforated sideshields.

OTHER PRECAUTIONS: Intentional misuse by deliberately concentrating and inhaling the contents can be harmful or fatal.

9. PHYSICAL AND CHEMICAL PROPERTIES

BOILING POINT: <0 to 412°F <-18 to 211°C

PRODUCT WEIGHT: 5.79 lb/gal 693 g/l

VAPOR DENSITY (AIR = 1): Heavier than air

SOLUBILITY IN WATER: N/A

PERCENT VOLATILE BY VOLUME: 99%

APPEARANCE AND ODOR: White / Baby Powder

SPECIFIC GRAVITY (H₂O = 1): 0.70

MELTING POINT: N/A

EVAPORATION RATE (BUTYL ACETATE = 1): Faster than ether

FORM: Liquid

VOLATILE ORGANIC COMPOUNDS (VOC Theoretical):

Volatile Weight 31.82% Less Water and Federally Exempt Solvents

10. STABILITY AND REACTIVITY

STABILITY: Stable

CONDITIONS TO AVOID: None known.

HAZARDOUS POLYMERIZATION: Will not occur

INCOMPATIBILITY (MATERIALS TO AVOID): None known.

HAZARDOUS DECOMPOSITION OR BYPRODUCTS: By fire: Carbon Dioxide, Carbon Monoxide

11. TOXICOLOGICAL INFORMATION

CAS NO. INGREDIENT NAME

74-98-6 Propane LC50 RAT 4 HR Not Available

LD50 RAT Not Available

106-97-8 Butane LC50 RAT 4 HR Not Available

LD50 RAT Not Available

CAS NO. INGREDIENT NAME

67-64-1 Acetone LC50 RAT 4 HR Not Available

LD50 RAT 5800 mg/kg

Proprietary Odorant LC50 RAT 4 HR Not Available

LD50 RAT Not Available

CARCINOGENICITY: NTP: Not Listed

IARC MONOGRAPH: Not Listed

OSHA REGULATED: Not Regulated

CALIFORNIA PROPOSITION 65:

WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.

TERATOLOGY: No data available.

REPRODUCTION: No data available.

MUTAGENICITY: No data available.

12. ECOLOGICAL INFORMATION

ECOTOXICOLOGICAL INFORMATION: No data available.

CHEMICAL FATE INFORMATION: No data available.

13. DISPOSAL CONSIDERATIONS

RCRA HAZARD CLASS: No data available.

WASTE DISPOSAL METHOD: Waste from this product may be hazardous as defined under the Resource Conservation and Recovery Act (RCRA) 40 FR 261. Waste must be tested for ignitability to determine the applicable EPA hazardous waste numbers. Do not incinerate. Depressurize container. Dispose of in accordance with Federal, State/Provincial, and Local regulations regarding pollution.

14. TRANSPORT INFORMATION

TRANSPORTATION REQUIREMENTS (49CFR172-101)

D.O.T. CLASSIFICATION: Consumer Commodity ORM-D

D.O.T. SHIPPING NAME: None

15. REGULATORY INFORMATION

EXPOSURE LIMITS: No data available.

16. OTHER INFORMATION

The information contained herein is based on data considered accurate. However, no warranty is expressed or implied regarding the accuracy of these data or the results to be obtained from the use thereof. Vendor assumes no responsibility for injury to vendee or third persons proximately caused by the material if reasonable safety procedures are not adhered to as stipulated in this MSDS. Additionally, vendor assumes no responsibility for injury to vendee or third persons proximately caused by abnormal use of the material even if reasonable safety procedures are followed. Furthermore, vendee assumes the risk in his use of the material.

N/D — NOT DETERMINED N/A — NOT APPLICABLE N/R — NOT REGULATED

Conforms to 29 CFR 1910.1200, OSHA

ANSI Z129.1 - 1988 American National Standard for Hazardous Industrial Chemicals