



# MATERIAL SAFETY DATA SHEET

**CHROMATE INDUSTRIAL CORPORATION®**  
5250-A Naiman Parkway, Solon, OH 44139 • 888-567-2206 • www.chromate.com

**FOR CHEMICAL  
EMERGENCY**

Call ChemTrec day/night:  
**1-800-424-9300**

## SECTION 1 – PRODUCT AND COMPANY IDENTIFICATION

**PRODUCT NAME:** RED LION PENETRATING OIL  
**PART NUMBER:** 74101

**DATE PREPARED:** APRIL 30, 2009

**PRODUCT TYPE:** LUBRICANT

**CHROMATE INDUSTRIAL CORPORATION**  
5250-A Naiman Parkway, Solon, OH 44139 • (888) 567-2206

## SECTION 2 – COMPOSITION / INFORMATION ON INGREDIENTS

| %<br>BY WEIGHT | CAS NUMBER | INGREDIENT                     | UNITS   | VAPOR<br>PRESSURE |
|----------------|------------|--------------------------------|---|-------------------|
| 8              | 74-98-6    | PROPANE                        | ACGIH TLV 2500 ppm<br>OSHA PEL 1000 ppm                                       | 760 mm            |
| 7              | 106-97-8   | BUTANE                         | ACGIH TLV 800 ppm<br>OSHA PEL 800 ppm   | 760 mm            |
| 8              | 64742-88-7 | MINERAL SPIRITS 140-FLASH      | ACGIH TLV 100 ppm<br>OSHA PEL 100 ppm   | 0.5 mm            |
| 15             | 8008-20-6  | KEROSINE, PETROLEUM            | ACGIH TLV Not Available<br>OSHA PEL Not Available                             | 0.7 mm            |
| 50             | 64742-52-5 | HEAVY NAPHTHENIC PETROLEUM OIL | ACGIH TLV Not Available<br>OSHA PEL Not Available                             |                   |
| 1              | 64742-65-0 | HEAVY PARAFFINIC OIL           | ACGIH TLV 5 mg/m <sup>3</sup> as Mist<br>OSHA PEL 5 mg/m <sup>3</sup> as Mist |                   |
| 10             | 111-76-2   | 2-BUTOXYETHANOL                | ACGIH TLV 20 ppm<br>OSHA PEL 25 ppm   | 0.88 mm           |

## SECTION 3 – HAZARDS IDENTIFICATION

**HMIS CODES:** HEALTH: 2 FLAMMABILITY: 4 REACTIVITY: 0

### ROUTES OF EXPOSURE

**INHALATION** of vapor or spray mist.

**EYE OR SKIN CONTACT** with the product, vapor or spray mist. Contains alcohols and acetates which can be absorbed through the skin.

### EFFECTS OF OVER-EXPOSURE

**EYES:** Irritation.

**SKIN:** Prolonged or repeated exposure may cause irritation.

**INHALATION:** Irritation of the upper respiratory system.

May cause nervous system depression. Extreme overexposure may result in unconsciousness and possibly death.

Prolonged overexposure to solvent ingredients in Section 2 may cause adverse effects to the liver, urinary, cardiovascular and reproductive systems.

**SIGNS AND SYMPTOMS OF OVER-EXPOSURE:** Headache, dizziness, nausea, and loss of coordination are indications of excessive exposure to vapors or spray mists. Redness and itching or burning sensation may indicate eye or excessive skin exposure.

**MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE:** None generally recognized.

**CANCER INFORMATION:** For complete discussion of toxicology data refer to Section 11.

**SECTION 4 – FIRST AID MEASURES**

**EYES:** Flush eyes with large amounts of water for 15 minutes. Get medical attention.

**SKIN:** Wash affected area thoroughly with soap and water. Remove contaminated clothing and launder before re-use.

**INHALATION:** If affected, remove from exposure. Restore breathing. Keep warm and quiet.

**INGESTION:** *DO NOT INDUCE VOMITING.* Get medical attention immediately.

**SECTION 5 – FIRE - FIGHTING MEASURES**

**FLASH POINT:** Propellant < 0°F

**FLAMMABLE LIMITS:**      **LEL:** 0.7              **UEL:** 10.6

**EXTINGUISHING MEDIA:** Carbon Dioxide, Dry Chemical, Foam

**UNUSUAL FIRE AND EXPLOSION HAZARDS:** Containers may explode when exposed to extreme heat. Application to hot surfaces requires special precautions. During emergency conditions overexposure to decomposition products may cause a health hazard. Symptoms may not be immediately apparent. Obtain medical attention.

**SPECIAL FIRE-FIGHTING PROCEDURES:** Full protective equipment including self-contained breathing apparatus should be used. Water spray may be ineffective. If water is used, fog nozzles are preferable. Water may be used to cool closed containers to prevent pressure build-up and possible autoignition or explosion when exposed to extreme heat.

**SECTION 6 – ACCIDENTAL RELEASE MEASURES**

**STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:**

- \* Remove all sources of ignition. Ventilate the area.
- \* Remove with inert absorbent.

**SECTION 7 – HANDLING AND STORAGE**

**STORAGE CATEGORY:** Not Available

**PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE:** Keep away from heat, sparks, and open flame. Vapors will accumulate readily and may ignite explosively.  
*During use and until all vapors are gone:* Keep area ventilated - Do not smoke - Extinguish all flames, pilot lights, and heaters - Turn off stoves, electric tools and appliances, and any other sources of ignition.

Consult NFPA Code. Use approved Bonding and Grounding procedures.

Contents under pressure. Do not puncture, incinerate, or expose to temperature above 120°F. Heat from sunlight, radiators, stoves, hot water, and other heat sources could cause container to burst. Do not take internally. Keep out of the reach of children.

**SECTION 8 – EXPOSURE CONTROLS / PERSONAL PROTECTION**

**PRECAUTIONS TO BE TAKEN IN USE:** Use only with adequate ventilation. Avoid contact with skin and eyes. Avoid breathing vapor and spray mist. Wash hands after using.

**VENTILATION:** Local exhaust preferable. General exhaust acceptable if the exposure to materials in Section 2 is maintained below applicable exposure limits. Refer to OSHA Standards 1910.94, 1910.107, 1910.108.

**RESPIRATORY PROTECTION:** If personal exposure cannot be controlled below applicable limits by ventilation, wear a properly fitted organic vapor/particulate respirator approved by NIOSH/MSHA for protection against materials in Section 2.

**PROTECTIVE GLOVES:** None required for normal application of aerosol products where minimal skin contact is expected. For long or repeated contact, wear chemical resistant gloves.

**EYE PROTECTION:** Wear safety spectacles with unperforated sideshields.

**OTHER PROTECTIVE EQUIPMENT:** Use of barrier cream on exposed skin is recommended.

**OTHER PRECAUTIONS:** Intentional misuse by deliberately concentrating and inhaling the contents can be harmful or fatal.

**SECTION 9 – PHYSICAL / CHEMICAL PROPERTIES**

**PRODUCT WEIGHT:** 6.64 lb/gal; 796 g/l

**SPECIFIC GRAVITY:** 0.80

**BOILING POINT:** <0 - 572°F / <-18 - 300°C

**MELTING POINT:** N/A

**VOLATILE VOLUME:** 54%

**EVAPORATION RATE:** Faster than ether

**VAPOR DENSITY:** Heavier than air

**SOLUBILITY IN WATER:** N/A

**VOLATILE ORGANIC COMPOUNDS (VOC Theoretical - As Packaged):** Volatile Weight 48.53% Less Water and Federally Exempt Solvents

**SECTION 10 – STABILITY AND REACTIVITY**

**STABILITY:** Stable

**CONDITIONS TO AVOID:** None known.

**INCOMPATIBILITY:** None known.

**HAZARDOUS DECOMPOSITION PRODUCTS:** *BY FIRE:* Carbon Dioxide, Carbon Monoxide

**HAZARDOUS POLYMERIZATION:** Will not occur.

**SECTION 11 – TOXICOLOGICAL INFORMATION**

**CHRONIC HEALTH HAZARDS:** No ingredient in this product is an IARC, NTP or OSHA listed carcinogen.  
 Reports have associated repeated and prolonged overexposure to solvents with permanent brain and nervous system damage.

**TOXICOLOGY DATA**

| CAS NO.    | INGREDIENT NAME                |                      |     |           |
|------------|--------------------------------|----------------------|-----|-----------|
| 74-98-6    | PROPANE                        | LC <sub>50</sub> RAT | 4HR | N/A       |
|            |                                | LD <sub>50</sub> RAT |     | N/A       |
| 106-97-8   | BUTANE                         | LC <sub>50</sub> RAT | 4HR | N/A       |
|            |                                | LD <sub>50</sub> RAT |     | N/A       |
| 64742-88-7 | MINERAL SPIRITS 140-FLASH      | LC <sub>50</sub> RAT | 4HR | N/A       |
|            |                                | LD <sub>50</sub> RAT |     | N/A       |
| 8008-20-6  | KEROSINE, PETROLEUM            | LC <sub>50</sub> RAT | 4HR | N/A       |
|            |                                | LD <sub>50</sub> RAT |     | N/A       |
| 64742-52-5 | HEAVY NAPHTHENIC PETROLEUM OIL | LC <sub>50</sub> RAT | 4HR | N/A       |
|            |                                | LD <sub>50</sub> RAT |     | N/A       |
| 64742-65-0 | HEAVY PARAFFINIC OIL           | LC <sub>50</sub> RAT | 4HR | N/A       |
|            |                                | LD <sub>50</sub> RAT |     | N/A       |
| 111-76-2   | 2-BUTOXYETHANOL                | LC <sub>50</sub> RAT | 4HR | N/A       |
|            |                                | LD <sub>50</sub> RAT |     | 470 mg/kg |

**SECTION 12 – ECOLOGICAL INFORMATION**

**ECOTOXICOLOGICAL INFORMATION:** N/A

**SECTION 13 – DISPOSAL CONSIDERATIONS**

**WASTE DISPOSAL METHOD:** Waste from this product may be hazardous as defined under the Resource Conservation and Recovery Act (RCRA) 40 CFR 261.  
 Waste must be tested for ignitability to determine the applicable EPA hazardous waste numbers.  
 Do not incinerate. Depressurize container. Dispose of in accordance with Federal, State/Provincial, and Local regulations regarding pollution.

**SECTION 14 – TRANSPORT INFORMATION**

**US Ground (DOT):** May be classed as Consumer Commodity, ORM-D  
 UN1950, AEROSOLS, 2.1, LIMITED QUANTITY, (ERG#126)

**Canada (TDG):** May be classed as Consumer Commodity, ORM-D  
 UN1950, AEROSOLS, CLASS 2.1, LIMITED QUANTITY, (ERG#126)

**IMO:** May be shipped as Limited Quantity  
 UN1950, AEROSOLS, CLASS 2.1, LIMITED QUANTITY, EmS F-D, S-U

**SECTION 15 – REGULATORY INFORMATION**

**SARA 313 (40 CFR 372.65C) SUPPLIER NOTIFICATION**

| CAS NO. | CHEMICAL/COMPOUND | % BY WT | % ELEMENT |
|---------|-------------------|---------|-----------|
|         | GLYCOL ETHERS     | 10      |           |

**CALIFORNIA PROPOSITION 65**

**WARNING:** This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.

**TSCA CERTIFICATION:** All chemicals in this product are listed, or are exempt from listing, on the TSCA Inventory.

**SECTION 16 – OTHER INFORMATION**

This product has been classified in accordance with the hazard criteria of the Canadian Controlled Products Regulations (CPR) and the MSDS contains all of the information required by the CPR. The above information pertains to this product as currently formulated, and is based on the information available at this time. Addition of reducers or other additives to this product may substantially alter the composition and hazards of the product. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.