



MATERIAL SAFETY DATA SHEET

CHROMATE INDUSTRIAL CORPORATION®

5250-A Naiman Parkway, Solon, OH 44139 • 888-567-2206 • www.chromate.com

**FOR CHEMICAL
EMERGENCY**

Call ChemTrec day/night:
1-800-424-9300

SECTION 1 – PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: RED LION CHAIN LUBE
PART NUMBER: 74119
PRODUCT TYPE: LUBRICANT
CHEM. FAMILY: PETROLEUM MIXTURE

DATE PREPARED: March 23, 2009

CHROMATE INDUSTRIAL CORPORATION

5250-A Naiman Parkway, Solon, OH 44139 • (888) 567-2206

SECTION 2 – COMPOSITION / DATA ON COMPONENTS

HAZARDOUS INGREDIENTS	%	EXPOSURE LIMIT	C.A.S.#	LD ₅₀ , ROUTE,SPECIES	LC ₅₀ ROUTE,SPECIES
PETROLEUM OIL BLEND (MIXTURE)	30-60	5 mg/m ³	64742-52-5	N/A	N/A
RESIDUAL OILS, PETROLEUM, SOLVENT DEWAXED	30-60	5 mg/m ³	64742-62-7	N/A	N/A
ISOBUTANE	1-5	1000 ppm	75-28-5	N/A	142,500 ppm (4h) INHAL -RAT
PROPANE	3-7	1000 ppm	74-98-6	N/A	N/A

SECTION 3 – HAZARDS IDENTIFICATION

ROUTE OF ENTRY

INGESTION: May cause headache, nausea, vomiting and weakness.

INHALATION: Inhalation of solvents may cause irritation. Propellant is a simple asphyxiant.

EYE CONTACT: May cause irritation.

SKIN ABSORPTION: No data available for this product mixture.

SKIN CONTACT: May cause irritation.

EFFECTS OF ACUTE EXPOSURE: Dizziness, nausea, irritation to skin and eyes.

EFFECTS OF CHRONIC EXPOSURE: Solvents may cause defatting dermatitis.

EXPOSURE LIMIT OF MATERIAL: See Section 2.

SECTION 4 – FIRST AID MEASURES

EMERGENCY FIRST AID PROCEDURE: In case of eye contact, flush immediately with plenty of water for at least 15 minutes and get medical attention. For skin, wash thoroughly with soap and water. If affected by inhalation of vapor of spray mist, remove to fresh air. If swallowed, **DO NOT INDUCE VOMITING**. Get medical attention.

SECTION 5 – FIRE-FIGHTING MEASURES

AUTO-IGNITION TEMPERATURE (°C): N/A

SPECIAL PROCEDURES: Water from fogging nozzles may be used to cool closed containers to prevent build-up if exposed to extreme temperatures. Full protective equipment including self-contained breathing apparatus should be worn in a fire involving this material.

FLAMMABILITY: Non-flammable Aerosol.

IF YES, UNDER WHICH CONDITIONS? N/A

EXTINGUISHING MEDIA: Water, Carbon Dioxide, Dry Chemical, Foam.

UPPER FLAMMABLE LIMIT: (% BY VOLUME): 9.5

LOWER FLAMMABLE LIMIT: (% BY VOLUME): 1.8

EXPLOSION DATA

SENSITIVITY TO DISCHARGE: N/A

SENSITIVITY TO IMPACT: N/A

HAZARDOUS COMBUSTION PRODUCTS: Hydrocarbon fumes and smoke. Carbon Monoxide where combustion is incomplete.

AEROSOL FLAME PROJECTION CLASSIFIED AS: 0 cm

FLASHBACK: None

FLASH POINT (°C) TAG CLOSED-CUP (CONCENTRATE): -142°F TCC

N/A — NOT APPLICABLE
N/L — NOT LISTED

N/D — NOT DETERMINED

N/E — NONE ESTABLISHED

N/R — NOT REGULATED

SECTION 6 – ACCIDENTAL RELEASE MEASURES

LEAK/SPILL: Remove all sources of ignition. Use an inert absorbent material, and use non-sparking tools. Ventilate area. Prevent from entering a watercourse.

SECTION 7 – HANDLING AND STORAGE

STORAGE NEEDS: Keep away from heat, sparks and open flames.

ENGINEERING CONTROLS: Ventilation-local (Mechanical if used indoors on a continuous basis.)

HANDLING PROCEDURES AND EQUIPMENT: Store in a cool, well ventilated area not to exceed 50°C.

SYNERGISTIC MATERIALS: None known.

SECTION 8 – EXPOSURE CONTROLS AND PERSONAL PROTECTION

GLOVES/TYPE: Wear chemical resistant gloves.

RESPIRATORY/TYPE: If used indoors on a continuous basis, use of a cartridge-type respirator (NIOSH/MSHATC 23C or equivalent) is recommended.

EYE/TYPE: Safety glasses.

FOOTWEAR/TYPE: Not normally required.

OTHER/TYPE: Not required.

SECTION 9 – PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL STATE: Aerosol

ODOR: Petroleum

VAPOR PRESSURE (PSIG)-AEROSOL@20°C: 55-65

EVAPORATION RATE (n-BUTYL ACETATE=1): <1

SOLUBILITY IN WATER g/L (20°C): Negligible

SPECIFIC GRAVITY (LIQUID): 0.85-0.95

FREEZING POINT (°C): N/A

SPECIFIC GRAVITY (AEROSOL): 0.81-0.92

APPEARANCE: Dark amber

ODOR THRESHOLD: N/A

BOILING POINT (°C)(CONCENTRATE): N/A

VAPOR DENSITY (AIR = 1): N/A

pH: N/A

CO-EFFICIENT OF WATER/OIL DISTRIBUTION: N/A

AEROSOL PERCENT VOLATILE (BY WEIGHT): N/A

SECTION 10 – STABILITY AND REACTIVITY DATA

HAZARDOUS PRODUCTS OF DECOMPOSITION: Hydrocarbon fumes and smoke. Carbon monoxide where combustion is incomplete.

CHEMICAL STABILITY: Yes, under normal conditions.

COMPATIBILITY WITH OTHER SUBSTANCES:

NO, WHICH ONES? Oxidizing Agents

REACTIVITY CONDITIONS: N/A

HAZARDOUS POLYMERIZATION: Will not occur.

SECTION 11 – TOXICOLOGICAL INFORMATION

REPRODUCTIVE EFFECTS: No information is available and no adverse reproductive effects are anticipated.

IRRITANCY OF MATERIAL: May cause irritation.

SENSITIZING CAPABILITY OF MATERIAL: Unknown.

CARCINOGENICITY OF MATERIAL: The ingredients of this product are not listed as carcinogens by NTP (National Toxicology Program), not regulated as carcinogens by OSHA (Occupational Safety and Health Administration), and have not been evaluated by IARC (International Agency for Research on Cancer), nor by ACGIH (American Conference of Governmental Industrial Hygienists).

TERATOGENICITY: No information is available and no adverse teratogenic effects are anticipated.

MUTAGENICITY: No information is available and no adverse mutagenic effects are anticipated.

SECTION 12 – ECOLOGICAL INFORMATION

ENVIRONMENTAL: N/A

N/A — NOT APPLICABLE
N/L — NOT LISTED

N/D — NOT DETERMINED

N/E — NONE ESTABLISHED

N/R — NOT REGULATED

SECTION 13 – DISPOSAL CONSIDERATIONS

WASTE DISPOSAL: Do not puncture or incinerate containers, even when empty. Dispose of in accordance with local, provincial and federal regulations.

SECTION 14 – TRANSPORT INFORMATION

DOT CLASSIFICATION: Consumer Commodity, ORM-D

TDG CLASSIFICATION: Consumer Commodity (AEROSOLS, UN 1950, Class 2.1)

SECTION 15 – REGULATIONS**CANADIAN REGULATIONS:**

WHMIS CLASSIFICATION: A,D2B.

CNFC SECTION 3.3.5: LEVEL 3

CEPA (CANADIAN ENVIRONMENTAL PROTECTION ACT): All substances in this product are listed on the CANADIAN DOMESTIC SUBSTANCES LIST (DSL) or not required to be listed.

U.S. REGULATIONS:

HMIS RATING HEALTH: 1 SLIGHT HAZARD

HMIS RATING FLAMMABILITY: 4 SEVERE HAZARD

HMIS RATING REACTIVITY: 0 MINIMAL HAZARD

HMIS RATING PERSONAL PROTECTION: B

NFPA CODE 30B: LEVEL 3

SARA 313 INFORMATION: THIS PRODUCT CONTAINS NO INGREDIENTS SUBJECT TO THE REPORTING REQUIREMENTS OF SECTION 313 OF THE EMERGENCY PLANNING AND COMMUNITY RIGHT-TO-KNOW ACT OF 1986 AND OF 40 CFR 372.

CALIFORNIA PROPOSITION 65:

WARNING: THIS PRODUCT DOES NOT INTENTIONALLY CONTAIN ANY CHEMICALS KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER, BIRTH DEFECTS OR OTHER REPRODUCTIVE HARM.

TSCA (Toxic Substances Control Act): All components of this product are listed on the TSCA Inventory. Any impurities present in this product are exempt from listing.

VOC (w/w%): <30

SECTION 16 – OTHER INFORMATION

THE INFORMATION ON THIS MATERIAL SAFETY DATA SHEET IS PROVIDED BY CHROMATE INDUSTRIAL CORPORATION (CIC) FREE OF CHARGE. WHILE BELIEVED TO BE RELIABLE, IT IS INTENDED FOR USE BY SKILLED PERSONS AT THEIR OWN RISK. CIC ASSUMES NO RESPONSIBILITY FOR EVENTS RESULTING OR DAMAGES INCURRED FROM ITS USE. THE INFORMATION ON THIS MATERIAL SAFETY DATA SHEET RELATES ONLY TO THE SPECIFIC MATERIAL DESIGNATED HEREIN AND DOES NOT RELATE TO USE IN COMBINATION WITH ANY OTHER MATERIAL OR IN ANY PROCESS.