



MATERIAL SAFETY DATA SHEET

CHROMATE INDUSTRIAL CORPORATION®

5250-A Naiman Parkway, Solon, OH 44139 • 888-567-2206 • www.chromate.com

**FOR CHEMICAL
EMERGENCY**

Call ChemTrec day/night:
1-800-424-9300

SECTION 1 – PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: BABY POWDER ODOR ELIMINATOR

DATE PREPARED: OCTOBER 15, 2008

PART NUMBER: 74166

PRODUCT TYPE: Acetone, Isobutane/propane blend

CHROMATE INDUSTRIAL CORPORATION

CHEMICAL FAMILY: Acetone, Isobutane/propane blend

5250-A Naiman Parkway, Solon, OH 44139 • (888) 567-2206

SECTION 1 – COMPOSITION, INFORMATION ON INGREDIENTS

NFPA RATING: HEALTH-1

FLAMMABILITY-3

REACTIVITY-0

SPECIAL---

HMIS RATING: HEALTH-1

FLAMMABILITY-3

REACTIVITY-0

PERSONAL PROTECTION-B

COMPONENTS- (Hazardous Components 1% or greater; Carcinogens 0.1% or greater)

COMPONENTS	CAS NO.	SARA III	OSHA	ACGIH	CARCINOGEN
Chemical/Common Names		LIST	PEL (PPM)	TLV (PPM)	REF. SOURCE **
ACETONE	67-64-1	No	1000	750	d
ISOBUTANE / PROPANE BLEND	75-28-5	No	800	800	d
	74-98-6	No	1000	1000	d

SECTION 2 – PHYSICAL/CHEMICAL CHARACTERISTICS

Boiling Point: N/A

Specific Gravity (H₂O=1): Concentrate Only = < 1

Vapor Pressure: PSIG @ 70°F (Aerosols): 50-60

Vapor Pressure (Non-Aerosols)(mm Hg and Temperature): N/A

Vapor Density (Air = 1): N/E

Evaporation Rate (= 1): N/E

Solubility in Water: Soluble

Water Reactive: No

Appearance and Odor: Clear liquid with fragrance.

SECTION 3 – FIRE AND EXPLOSION HAZARD DATA

FLAMMABILITY as per USA FLAME PROJECTION TEST (aerosols): flame projection with spray through cap: projection greater than 18" with flashback: Categorized as **EXTREMELY FLAMMABLE**

Auto-Ignition Temperature: N/E

Flammability Limits in Air by % in Volume: % LEL: N/E % UEL: N/E

FLASH POINT AND METHOD USED (non-aerosols): N/A

EXTINGUISHER MEDIA: Foam, dry chemical, carbon dioxide, water.

SPECIAL FIRE-FIGHTING PROCEDURES: Provide shielding for personnel. Wear self-contained breathing apparatus. Cool containers with water fog to prevent rupturing & spewing.

UNUSUAL FIRE & EXPLOSION HAZARDS: Do not expose aerosols to temperatures above 120°F or the container may rupture.

N/A — NOT APPLICABLE
N/L — NOT LISTED

N/D — NOT DETERMINED

N/E — NONE ESTABLISHED

N/R — NOT REGULATED

SECTION 4 – REACTIVITY HAZARD DATA

STABILITY: STABLE.

HAZARDOUS POLYMERIZATION: WILL NOT OCCUR.

INCOMPATIBILITY (MAT. TO AVOID): Alkalis, oxidizing materials, amines.

CONDITIONS TO AVOID: Open flame, welding arcs, heat.

HAZARDOUS DECOMPOSITION PRODUCTS: CO, CO₂.

SECTION 5 – HEALTH HAZARD DATA

PRIMARY ROUTES OF ENTRY: INHALATION

ACUTE EFFECTS Vapor concentrations around 1000 ppm may cause slight transient irritation to the upper respiratory tract.

Inhalation: Excessive inhalation of vapors can be harmful and may cause headache, dizziness, asphyxia, anesthetic effects and possible unconsciousness.

Eye Contact: Irritation.

Skin Contact: May cause slight irritation.

Ingestion: Possible chemical pneumonitis if aspirated into lungs. Nausea.

CHRONIC EFFECTS: (Effects due to excessive exposure to the raw materials of this mixture) May cause mucous membrane irritation, overnight headache, and general weakness.

Medical Conditions Generally Aggravated by Exposure: May aggravate existing eye, skin, or upper respiratory conditions.

EMERGENCY FIRST AID PROCEDURES

Eye Contact: Flush with water for 15 minutes. If irritated, seek medical attention.

Skin Contact: Wash with soap and water. If irritated, seek medical attention.

Inhalation: Remove to fresh air. Resuscitate if necessary. Get medical attention.

Ingestion: DO NOT INDUCE VOMITING. Drink two large glasses of water. Get immediate medical attention.

SECTION 6 – CONTROL AND PROTECTIVE MEASURES

Respiratory Protection (specify type): If vapor concentration exceeds TLV, use respirator approved by U.S. Bureau of Mines / NIOSH for organic vapor.

Protective Gloves: Latex, if skin easily irritated.

Eye Protection: Safety glasses recommended.

Ventilation Requirements: Adequate ventilation to keep vapor concentration below TLV.

Other Protective Clothing & Equipment: None

Hygienic Work Practices: Wash with soap and water before handling food. Remove contaminated clothing.

SECTION 7 – PRECAUTIONS FOR SAFE HANDLING AND USE

Steps To Be Taken If Material Is Spilled Or Released: Absorb with suitable medium. Incinerate or landfill according to local, state or federal regulations. DO NOT FLUSH TO SEWER.

Waste Disposal Methods: Aerosol cans when vented to atmospheric pressure through normal use, pose no disposal hazard.

Precautions To Be Taken In Handling & Storage: Do not puncture or incinerate containers. Do not store at temperatures above 120°F.

Other Precautions &/or Special Hazards: KEEP OUT OF REACH OF CHILDREN. Avoid food contamination. Avoid breathing vapors. Remove ignition sources.

OTHER INFORMATION

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind.

** Chemical Listed as Carcinogen or Potential Carcinogen. [a] NTP [b] IARC Monograph [c] OSHA [d] Not Listed [e] Animal Data Only