



# MATERIAL SAFETY DATA SHEET

**CHROMATE INDUSTRIAL CORPORATION®**

5250-A Naiman Parkway, Solon, OH 44139 • 888-567-2206 • www.chromate.com

**FOR CHEMICAL  
EMERGENCY**

Call ChemTrec day/night:  
**1-800-424-9300**

## SECTION 1 – PRODUCT AND COMPANY IDENTIFICATION

**PRODUCT NAME:** RED LION MULTI-PURPOSE

**DATE PREPARED:** April 14, 2009

SEALANT CLEAR

**PART NUMBER:** 74574

**CHROMATE INDUSTRIAL CORPORATION**

5250-A Naiman Parkway, Solon, OH 44139 • (888) 567-2206

## SECTION 2 – COMPOSITION / DATA ON COMPONENTS

**CHEMICAL DESCRIPTION:** This product is a mixture of the substances listed below with nonhazardous additions.

**DANGEROUS COMPONENTS:**

64742-89-8	VM&P NAPHTHA	14.8%
1317-65-3	CALCIUM CARBONATE	14.23%
108-88-3	TOLUENE	13.02%
142-82-5	HEPTANE	12.3%
74-98-6	PROPANE	11.33%
67-64-1	ACETONE	9.35%
106-97-8	N-BUTANE	6.66%
108-65-6	PM ACETATE	2.12%
1330-20-7	XYLENE (MIX)	1.63%

## SECTION 3 – HAZARDS IDENTIFICATION

**HAZARD DESCRIPTION:** HARMFUL, EXTREMELY FLAMMABLE

**PHYSICAL DANGERS:** EXTREMELY FLAMMABLE. IRRITATING TO EYES AND SKIN.

**HARMFUL:** DANGER OF SERIOUS DAMAGE TO HEALTH BY PROLONGED EXPOSURE THROUGH INHALATION.

KEEP OUT OF THE REACH OF CHILDREN.

**EFFECTS OF CHRONIC OVEREXPOSURE:** May cause permanent brain and nervous system damage. Repeated overexposure can also damage kidneys, lungs, liver, heart, and blood. Intentional misuse by deliberately inhaling the contents may be harmful or fatal.

**NFPA RATINGS (SCALE 0 - 4): HEALTH: 1**

**FIRE: 4**

**REACTIVITY: 3**

**HMIS-RATINGS (SCALE 0 - 4): HEALTH: 1**

**FIRE: 4**

**PHYSICAL HAZARD: 3**

## SECTION 4 – FIRST AID MEASURES

**INHALATION:** Supply fresh air; consult doctor in case of complaints.

**SKIN CONTACT:** Immediately wash with water and soap and rinse thoroughly.

**EYE CONTACT:** Move to fresh air. Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

**INGESTION:** Contact physician or poison control center.

## SECTION 5 – FIRE-FIGHTING MEASURE

**EXTINGUISHING AGENTS:** CO<sub>2</sub>, sand, extinguishing powder, or water spray. Fight larger fires with water spray or alcohol resistant foam.

**PROTECTIVE EQUIPMENT:** No special measures required.

**SECTION 6 – ACCIDENTAL RELEASE MEASURES**

**PERSONAL SAFETY PRECAUTIONS:** Wear protective equipment. Keep unprotected persons away.

**ENVIRONMENTAL SAFETY PRECAUTIONS:** Do not allow product to reach sewage systems or ground water.

**MEASURES FOR CLEANING/ COLLECTING:** Ensure adequate ventilation.

**SECTION 7 – HANDLING AND STORAGE**

**FIRE/EXPLOSION PROTECTION:** Do not spray on a naked flame or any incandescent material. Do not smoke. Protect from electrostatic discharges.

**STORAGE REQUIREMENTS:** Observe pressurized container storage regulations. Consult with your local authorities.

**SECTION 8 – EXPOSURE CONTROLS AND PERSONAL PROTECTION****COMPONENTS WITH LIMIT VALUES THAT REQUIRE MONITORING AT THE WORKPLACE:****108-88-3 TOLUENE**

*PEL* Short-term value: C 300; 500\* ppm

Long-term value: 200 ppm

**\*10-min peak per 8-hr shift**

*REL* Short-term value: 560 mg/m<sup>3</sup>, 150 ppm

Long-term value: 375 mg/m<sup>3</sup>, 100 ppm

*TLV* 75 mg/m<sup>3</sup>, 20 ppm

**142-82-5 HEPTANE**

*PEL* 2000 mg/m<sup>3</sup>, 500 ppm

*REL* Short-term value: C 1800\* mg/m<sup>3</sup>, C 440\* ppm

Long-term value: 350 mg/m<sup>3</sup>, 85 ppm

**\*15-min**

*TLV* Short-term value: 2050 mg/m<sup>3</sup>, 500 ppm

Long-term value: 1640 mg/m<sup>3</sup>, 400 ppm

**74-98-6 PROPANE**

*PEL* 1800 mg/m<sup>3</sup>, 1000 ppm

*REL* 1800 mg/m<sup>3</sup>, 1000 ppm

*TLV* Varies mg/m<sup>3</sup>, 1000 ppm

**67-64-1 ACETONE**

*PEL* 2400 mg/m<sup>3</sup>, 1000 ppm

*REL* 590 mg/m<sup>3</sup>, 250 ppm

*TLV* Short-term value: 1782 mg/m<sup>3</sup>, 750 ppm

Long-term value: 1188 mg/m<sup>3</sup>, 500 ppm

BEI

**106-97-8 N-BUTANE**

*REL* 1900 mg/m<sup>3</sup>, 800 ppm

*TLV* Varies mg/m<sup>3</sup>, 1000 ppm

**108-65-6 PM ACETATE**

*WEEL* 50 ppm

**1330-20-7 XYLENE (MIX)**

*PEL* 435 mg/m<sup>3</sup>, 100 ppm

*REL* Short-term value: 655 mg/m<sup>3</sup>, 150 ppm

Long-term value: 435 mg/m<sup>3</sup>, 100 ppm

*TLV* Short-term value: 651 mg/m<sup>3</sup>, 150 ppm

Long-term value: 434 mg/m<sup>3</sup>, 100 ppm

BEI

**PROTECTIVE HYGIENIC MEASURES:** Keep away from food stuffs and animal feed. Wash hands after use.

**BREATHING EQUIPMENT:** A respirator is generally not necessary when using this product outdoors or in large open areas. In cases where short and/or long term overexposure exists, a charcoal filter respirator should be worn. Please consult an authority on chemical hygiene monitoring if you suspect overexposure conditions exist and need a specific recommendation on proper ventilation techniques and personal protection.

**PROTECTION OF HANDS:** Protective gloves. The glove material has to be impermeable and resistant to the substance. No glove recommendation can be given.

**EYE PROTECTION:** Tightly sealed goggles

**SECTION 9 – PHYSICAL AND CHEMICAL PROPERTIES****GENERAL INFORMATION:****ODOR:** Aromatic**FLASH POINT:** -19°C**AUTO-IGNITING:** Product is not self-igniting.**DANGER OF EXPLOSION:** Stable at normal temperatures. Can may burst when exposed to temperatures exceeding 120°F.

In use, may form flammable/explosive vapor-air mixture.

**LOWER EXPLOSION LIMIT:** 0.9 Vol %**VAPOR PRESSURE:** 40 PSI, 2750 hPa**SPECIFIC GRAVITY:** Between 0.77 and 0.85 (Water equals 1.00)**VOC CONTENT (LESS EXEMPT SOLVENTS):** 63.6 %**MIR VALUE:** 1.46**BOILING POINT/BOILING RANGE:** -110°C**IGNITION TEMPERATURE:** 215°C**UPPER EXPLOSION LIMIT:** 10.9 Vol %**DENSITY AT 20°C:** 0.7452 g/cm<sup>3</sup>**VOC CONTENT:** 519.5 g/l / 4.34 lb/gl**MIR VALUE:** 63.6 %**SOLIDS CONTENT:** 30.8 %**SECTION 10 – STABILITY AND REACTIVITY DATA****CONDITIONS TO BE AVOIDED:** Do not allow the can to exceed 120°F. Stable at normal temperatures.**POSSIBILITY OF HAZARDOUS REACTIONS:** No dangerous reactions known.**SECTION 11 – TOXICOLOGICAL INFORMATION****PRIMARY EFFECT ON THE SKIN:** Irritant to skin and mucous membranes.**PRIMARY EFFECT ON THE EYE:** Irritating effect.**SENSITIZATION:** No sensitizing effects known.**ADDITIONAL TOXICOLOGICAL INFORMATION:** The product shows the following dangers according to internally approved calculation methods for preparations:**SECTION 12 – ECOLOGICAL INFORMATION****OTHER INFORMATION:** This product does not contain any chloroflourocarbons (CFC's),chlorinated solvents, lead, mercury, cadmium, hexavalent chromium, polybrominated biphenyl (PBB), or polybrominated diphenyl ether (PDBE). No specific ecological data is available for this product.**ACQUATIC TOXICITY:** Hazardous for water, do not empty into drains.**SECTION 13 – DISPOSAL CONSIDERATIONS****DISPOSAL METHOD:** Dispose of in accordance with local, state, and federal regulations. Do not puncture, incinerate, or compact. Partially empty cans must be disposed of responsibly. Do not heat or cut empty containers with electric or gas torches.**RECOMMENDATION:** Completely empty cans should be recycled.**SECTION 14 – TRANSPORT INFORMATION****HAZARD CLASS:** 2.1**LABEL:** 2.1**UN-NUMBER:** 1950**PACKAGING GROUP:** II**MARINE POLLUTANT:** No**PROPER SHIPPING NAME:** Aerosols, Flammable

Consumer Commodity ORM-D

**IDENTIFICATION NUMBER:** N/A**ADR/RID CLASS:** 2 5F Gases**IMDG CLASS:** 2.1**EMS NUMBER:** F-D,S-U**ICAO/IATA CLASS:** 2.1

## SECTION 15 – REGULATIONS

**SARA SECTION 355 (EXTREMELY HAZARDOUS SUBSTANCES):** None of the ingredients in this product are listed.

**SARA SECTION 313 (SPECIFIC TOXIC CHEMICAL LISTINGS):** 108-88-3 TOLUENE  
1330-20-7 XYLENE (MIX)

**TSCA (TOXIC SUBSTANCES CONTROL ACT):** All ingredients are listed.

**PROPOSITION 65 CHEMICALS KNOWN TO CAUSE CANCER:** 100-41-4 ETHYL BENZENE

**PROPOSITION 65 CHEMICALS KNOWN TO CAUSE DEVELOPMENTAL TOXICITY:** 108-88-3 TOLUENE

**EPA:** A: Known human carcinogen                      B: Probable human carcinogen  
C: Possible human carcinogen                      D: Not classifiable as to human carcinogenicity:  
Inadequate human and animal evidence of carcinogenicity (or no data is available).

108-88-3	TOLUENE	II
142-82-5	HEPTANE	D
67-64-1	ACETONE	I
1330-20-7	XYLENE (MIX)	I

**IARC:** Group 2B: The ingredient is possibly carcinogenic to humans. There is limited evidence of carcinogenicity.

Group 3: The ingredient is unclassifiable as to its carcinogenicity to humans.

108-88-3	TOLUENE	3
1330-20-7	XYLENE (MIX)	3

**ACGIH TLVs:**

A1-designates a confirmed human carcinogen.  
A2-designates a suspected human carcinogen.  
A3-designates an animal carcinogen.  
A4-designates "not classifiable as a human carcinogen".

108-88-3	TOLUENE	A4
67-64-1	ACETONE	A4
1330-20-7	XYLENE (MIX)	A4

**NIOSH:** None of the ingredients is listed.

**HAZARD SYMBOLS:** HARMFUL, EXTREMELY FLAMMABLE

**HAZARD-DETERMINING COMPONENTS OF LABELLING:** TOLUENE

**RISK PHRASES:** EXTREMELY FLAMMABLE. IRRITATING TO EYES AND SKIN.

**HARMFUL:** Danger of serious damage to health by prolonged exposure through inhalation.

**SAFETY PHRASES:** KEEP OUT OF THE REACH OF CHILDREN. Keep in a cool place. Keep container in a well-ventilated place.

Keep away from food, drink and animal feeding stuffs. Keep away from sources of ignition - No smoking. Do not breathe gas/fumes/vapour/spray. Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point. Wear suitable protective clothing and gloves. If swallowed, seek medical advice immediately and show this container or label. Use only in well-ventilated areas.

**SPECIAL LABELING OF CERTAIN PREPARATIONS:** KEEP OUT OF THE REACH OF CHILDREN.

## SECTION 16 – OTHER INFORMATION

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

**ABBREVIATIONS AND ACRONYMS:**

**ADR:** Accord européen sur le transport des marchandises Dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

**IATA:** International Air Transport Association

**GHS:** Globally Harmonized System of Classification and Labelling of Chemicals

**EINECS:** European Inventory of Existing Commercial Chemical Substances

**CAS:** Chemical Abstracts Service (division of the American Chemical Society)

**NFPA:** National Fire Protection Association (USA)

**VOC:** Volatile Organic Compounds (USA, EU)