

DOUBLE/BUBBLE® EPOXIES

Single Use Epoxy Assortment



DOUBLE/BUBBLE® EPOXY ASSORTMENT

P/N 17040

40



Double/Bubble Epoxy Extra Fast Setting
 • Extra fast setting for quick repairs
 • For bonding wood, glass, metal, stone, concrete, ceramics & leather
 P/N 74499



Double/Bubble Machineable Epoxy
 • Machineable tooling and/or body-patching adhesive
 • Adheres to metal, wood and hard plastics
 • Can be machined, sanded, drilled and tapped
 P/N 74498



Double/Bubble General Purpose Epoxy
 • A long work-life adhesive
 • For bonding wood, metal, ceramics, concrete, rubber & plastics
 P/N 74497



Double/Bubble High Peel Strength Epoxy
 • A flexible, tough & durable, vibration resistant adhesive
 • High peel and shear strengths
 • Bonds to polystyrene, ABS nylon, metal, wood, masonry and rubber
 P/N 74496



Double/Bubble Wet Surface Patching Epoxy
 • A gap-filling adhesive for use in damp or moist environments
 • Cures and bonds under water
 • Bonds to stone, concrete, metal, glass, china, wood and fiberglass
 P/N 74495



Double/Bubble Extra Fast Set (Non-Sag) Epoxy
 • A gap-filling adhesive for use in damp or moist environments
 • Cures and bonds under water
 • Bonds to stone, concrete, metal, glass, china, wood and fiberglass
 P/N 74495



CHROMATE INDUSTRIAL CORP.

P/N 17040

030110



P/N 17040



EXCEPTIONAL PRODUCTS, SERVICE AND INNOVATIVE SOLUTIONS

5250-A Naiman Parkway . Solon . OH 44139

1-800-BUY-BOLT . Fax: 631-567-2418 . www.chromate.com

030110

DOUBLE/BUBBLE® SINGLE USE EPOXY ADHESIVES



Double/Bubble® Epoxy Extra Fast Setting P/N 74499

- Extra fast setting for quick repairs
- For bonding wood, glass, metal, stone, concrete, ceramics & leather

Uses: Repairing tools, auto parts, electrical and electronic components, furniture and other applications that require a fast-setting adhesive.

Work time: 3 minutes

Handling strength: 15-30 minutes



Double/Bubble® Machineable Epoxy P/N 74498

- Machineable tooling and/or body-patching adhesive
- Adheres to metal, wood and hard plastics
- Can be machined, sanded, drilled and tapped

Uses: Patching and filling voids and scratches in plastic and metal tooling, patterns and furniture.

Work time: 25 minutes

Handling strength: 4 hours



Double/Bubble® General Purpose Epoxy P/N 74497

- A long work-life adhesive
- For bonding wood, metal, ceramics, concrete, rubber & plastics

Uses: Repair of tools, furniture and sports equipment. An excellent adhesive for use with fiberglass cloth.

Work time: 2 hours

Handling strength: 8 hours



Double/Bubble® High Peel Strength Epoxy P/N 74496

- A flexible, tough and durable, vibration resistant adhesive
- High peel and shear strengths
- Bonds to polystyrene, ABS nylon, metal, wood, masonry and rubber

Uses: For repair of sports equipment, marine, aircraft, auto, truck and tractor parts. Excellent adhesive for grinding wheel hubs, door and window gaskets.

Work time: 3 hours

Handling strength: 18 hours



Double/Bubble® Wet Surface Patching Epoxy P/N 74495

- A gap-filling adhesive for use in damp or moist environments
- Cures and bonds under water
- Bonds to stone, concrete, metal, glass, china, wood and fiberglass

Uses: Wet crack sealant and plumbing patch. For repair of gutters, battery cases and boats. Excellent adhesive for use with fiberglass tape.

Work time: 25 minutes

Handling strength: 5 hours




Double/Bubble® Water Clear Epoxy P/N 74494

- Use as an adhesive or coating
- Bonds to metal, ceramics, glass, porcelain and wood
- Covers and fills scratches
- Impact resistant

Uses: Repair of printed circuit boards (does not electrically corrode copper), optical fibers, lenses and other optical equipment, jewelry, art objects and other applications where a clear bond is desired.

Work time: 1 hour

Handling strength: 8 hours



Double/Bubble® Regular Setting Epoxy P/N 74493

- A low-viscosity adhesive
- Fairly long work-life
- Cures to a light color
- Bonds well to wood, metal, concrete, fabrics and most plastics

Uses: Excellent for applications requiring a thin glue line. Ideal for fine furniture, hobby use and sports equipment.

Work time: 45 minutes

Handling strength: 4 hours



Double/Bubble® Extra Fast Set (Non-Sag) Epoxy P/N 74492

- Extra fast setting
- Non-sag (thixotropic) adhesive
- For quick repairs
- Bonds to wood, glass, metal, stone, ceramics and leather

Uses: Ideal for quick, permanent, vertical and overhead repairs. For fixturing, tacking, sealing, gap filling and staking in electrical and industrial applications.

Work time: 3 minutes

Handling strength: 15-30 minutes

When it comes to MRO supplies, quality products make all the difference!



CUTTING TOOLS



CHEMICALS



SHOP SUPPLIES



FASTENERS



ELECTRICAL



WELDING



FLEET



HYDRAULICS



MEDICAL