



Prep-Solve

(Pre-paint surface cleaner)

Ideal for preparing surfaces prior to painting or bonding. This special formulation of virgin solvents is extremely effective in removing adhesives, tar, undercoating, rustproofing, waxes, Teflon® coatings, polishes, silicones, paint overspray, grease and sealants. Also ideal for spraying on “tack cloths” for dust removal just prior to painting.



P/N 74700 – 14.5 oz.

Features

- Special blend of hydrocarbon solvents swiftly cut through a wide range of dirt, grime and grease
- Deep cleaning action leaves no film or residue
- Does not inhibit the application of primers, paints and other protective coatings
- Significantly improves the adhesive quality of glues and cements on surfaces to be joined.

Applications

- Excellent for preparing surfaces prior to painting or bonding
- Cleans fragile automotive surfaces such as carpeting, vinyls, plastics and fabrics



PRO-COAT™ Acrylic Enamel Paints

(Extremely tough, corrosion resistant, fast drying paints)




Fast-drying, high solids formula ensures maximum coverage and durability on all metal and wood surfaces. Resists corrosion, chipping and peeling and the unique SprayPro™ nozzle makes application easy in both horizontal and vertical positions.

Features

- Fast-Drying
- Maximum Coverage
- Ultimate Protection
- Interior / Exterior
- SprayPro™ Nozzle

SprayPro™ Nozzle:



Gloss Black
P/N 74014 – 15.25 oz.

Gloss White
P/N 74010 – 15.25 oz.

Hi-Temp Flat Black
P/N 74016 – 15.25 oz.

Industrial Gray
P/N 74012 – 15 oz.

Gray Primer
P/N 74003 – 15.25 oz.

Applications

- Conduit
- Conveyors
- Doors
- Ducts
- Fencing
- Electrical Equipment
- Ladders
- Machinery
- Motors
- Pipelines
- Railings
- Shelving
- Tools
- Safety Markings



E-Z POXY 200

(For steel hard repairs in a stick)



P/N 74502 – 4 oz.

A combination of steel reinforced epoxy resin and hardener in a stick. Simply knead putty and apply to damaged area. It can be drilled, filed, tapped, sanded or machined after one hour.

Features

- No measuring, mess or waste
- Fast – sets in 10 minutes
- Adheres to damp surfaces and hardens under water
- Certified to NSF/ANSI Standard 61 for use in contact with potable water and drinking water systems
- Authorized by the USDA for use in federally inspected meat and poultry plants

Applications

- Perfect for repairing tanks, radiators, bathroom fixtures, tile, cars, boats, metal and wood furniture, downspouts, gutters, garbage cans, valves, cast iron, etc.

PHYSICAL PROPERTIES:

Density.....	18.5 lb./gal. (2.2 gm/cm ³)
Compression Strength.....	12,000 psi
Tensile Strength.....	6,000 psi
Modulus of Elasticity.....	6 x 10 ⁵ psi
Adhesive Strength	900 psi
Izod Impact.....	0.3 ft.-lb./in. (notched)
Hardness (Shore D).....	80
Maximum Use Temp.....	300°F (149°C)

ELECTRICAL PROPERTIES:

Volume Resistance.....	1 x 10 ¹² ohm-cm
Dielectric Strength....	300 volts/mil @ 0.15 cm

IMPORTANT: Do not use on polyethylene, polypropylene and polybutylene.



Instant Adhesive

(High strength, cyanoacrylate adhesive for non-porous surfaces)

Ultra-high performance, versatile adhesive bonds metal, rubber, plastic and glass instantly. Red Lion Instant Adhesive works where others fail, providing the strongest bond on hard-to-bond surfaces.



P/N 74516 – 1/3 fl. oz.

Features

- Permanent, super strength bond
- Easy to use
- Bonds instantly
- Saves time, money, labor and mess

Applications

- Bonds metal, rubber, plastic and glass

TECHNICAL DATA:

Color	Clear
Gap Fill004"
Viscosity cP	40
Tensile Shear Strength PSI	2,500
Temperature	
Range	-65°F to 180°F (-54°C to 82°C)
Cure Speed	
Fixture.....	20-40 seconds
Full.....	24 hours